MANURE MANAGEMENT EQUIPMENT



KEEP REENGINEERING, KEEP INNOVATING

Manure Collector

It is quick and efficient in collecting poultry

Litter time efficient

Simple to operate

Easy to maneuver

Best reliability



Good mobility & operation.



Easily disassembled & maintain.



Best reliability in harsh working environment.



Specification of Manure Collector

Machine Dimension : L 2000 m/m x W 900m/m x H 1540m/m

Feeding : Feeding Width: 860m/m

Bag Loading : 240bags in an hour; 15 seconds/pack

Working Speed : Low Speed 5.7 m/minute

High Speed 11.2 m/minute

Power : HONDA electronic firing 6.5HP engine

Net Weight : 218kg

Litter Raking Machine

Easy 3 - Step Start

Easy start technology simplifies pull starts to 3 steps.

User - Friendly Design

Flexible shaft design makes it easier to trim under bushes and hard to reach places while the quick change head allows you to convert from bump head to blade in seconds saving you time.

Powerful Machine

43cc full crank 2 cycle engine provides greater power and less vibration to give you control.

Heavy Duty Metal Blade

Heavy duty metal blade and cutting width allows you to cut through dense manure in less time.



TYPE OF BLADE



Specification of Litter Raking Machine

Power Type Petrol

Two Stroke, One Cylinder, air cooling **Engine Type**

2.7HP Power **Fuel Tank** 1.2liter **Rated Speed** 7000 r/min Back-pack type

Mitsubishi Heavy Industries Ltd. **Engine manufacture**

Carburetor MHI Japan (Float type)

Ignition system Transistorized flywheel magneto

Main pipe 24mm x 1500mm

Dimension (LxWxH) 2800mm x 370mm x 440mm

Pristine Glory Sdn. Bhd. **Poultry Equipment Manufacturer** (Co. No.: 353246-W)

PT8638, Jalan Johan 2/6, Kawasan Perindustrian Pengkalan, Fasa 2, 31550 Pusing, Perak Darul Ridzuan, Malaysia

